

Teknik Veriler / Technical Data



Çalışma gerilimi
Operating voltage
Max 300 V



Çalışma sıcaklığı
Operating temperature
-30°C..+ 70°C



Bükme yarıçap
Bending radius
Min. 7,5 x Ø




Test gerilimi
Test voltage
2500 V



İzolasyon direnci
Insulation resistance
<200 Mohm x Km

KTSxxxx FRNC HOPARLÖR KABLOSU



Kullanım Alanları

Profesyonel seslendirmede güçlü, esnek yapısı ile sahne ve sabit sistemlerde tercih edilir. Düşük iletken dirençli OFC bakırlardan değişken güçlerin iletimi için iki eş eksensli olarak farklı kesitlerde dizayn edilirler. Esnek yapısını meydana getiren kaliteli malzemelerin birleşimi ile mekanik dayanımı maksimum seviyededir. HFFR dış kılıf sayesinde geç tutuşur, yanma esnasında zehirli gaz çıkarmazlar.

Applications

These cables are designed double axes at different sections with low OFC conductor resistance and used for stage and stable professional sound systems. They have maximum mechanical strength with their flexible construction. During combustion, the halogen-free insulation materials produces neither corrosive nor toxic gases.

Kablo Yapısı / Cable Structure		Uygulanan Testler / Applied Tests				
İletken Conductor	: Tavlı bükülü bakır tel (HD 383 S2 Class 6) : Annealed stranded copper wire (HD 383 S2 Class 6)				Yapısal boyut testleri Structural dimension tests	: EN 60811-1-1
İzolasyon Insulation	: HFFR bileşik : HFFR compound				Mekanik testler Mechanical tests	: EN 50289-3, EN 50290-2
Damar tanımlama Core identification	: Renk kodlu : Color coded				Elektriksel testler Electrical tests	: EN 50289-1
Kılıf Sheath	: Esnek mat HFFR bileşik : Flexible matt HFFR compound				Çevre şartları testleri Environmental tests	: EN 50289-4
	KTS 2150 FRNC	KTS 2250 FRNC	KTS 2400 FRNC	KTS 4400 FRNC	Yangın performans testleri Fire performance tests	: IEC60332-1, EN50265-2-1
İletken Inner Conductor	84x0,15 mmØ 2x1,50 m ²	140x0,15 mmØ 2x2,50 m ²	225x0,15 mmØ 2x4 m ²	225x0,15 mmØ 4x4 m ²		
Dış Çap Outer Diameter	6,9 ± 0,2 m	8 ± 0,2 mmØ	9,7 ± 0,2 mmØ	11,5 ± 0,2 mmØ		
Renk Color	: Siyah : Black					

* Standart ambalajlama
100 mt ye kadar Karton yada PVC makara, 100 mt den fazla boylar uygun PW makaralarda

* Standard packaging
Up to 100 mt cardboard or PVC Spool, more than 100 mt suitable PW Drums