

## Teknik Veriler / Technical Data



**Test gerilimi**  
**Test voltage**  
Damar/Damar 500 Veff  
Damar/Ekran 1500 Veff  
Core/Core 500 Veff  
Core/Shld 1500 Veff



**Çalışma sıcaklığı**  
**Operating temperature**  
-30°C., + 70°C



**Kablo ağırlığı**  
**Cable weight**  
15 Kg/Km.



**İletken direnci**  
**Conductor Resistance**  
<90 Ω/Km



**İzolasyon direnci**  
**Insulation resistance**  
>1GΩxKm



**Kapasite**  
**Capacitance**  
Damar/Damar <80 nF/Km  
Damar/Ekran <150 nF/Km  
Core/Core <80 nF/Km  
Core/Shld <150 nF/Km



**Ekran direnci**  
**Shield Resistance**  
<22 Ω/Km

## KP 2230



### Kullanım Alanları

Profesyonel seslendirme sistem montajlarında, rack içlerinde veya sabit sitemlerde düşük çaplı, esnek yapısı ile tercih edilen mini folyo ekranlı mikrofon montaj kablodur.

### Applications

These cables are flexible mini foil shielded microphone montage cables and used inside of rack, Professional sound system montages and stable installations.

### Kablo Yapısı / Cable Structure

<b>İletken</b> Conductor	: Bükülü kalaylı bakır teller (0.22 mm <sup>2</sup> ) : Stranded tinned copper wires (0.22 mm <sup>2</sup> )
<b>İzolasyon</b> Insulation	: PP bileşik (Ø1.1mm) : PP compound (Ø0.72mm)
<b>Ekranlama</b> Shielding	: Toprak teli ile birlikte Helisel sarılmış Al-pes folyo : Helical wrapped Al-pes foil with drain wire
<b>Kılıf</b> Sheath	: Esnek mat PVC bileşik (Ø 32 mm) : Flexible matt PVC compound (Ø 32 mm)
<b>Renk</b> Color	: Siyah yada Gri : Black or Gray

### Uygulanan Testler / Applied Tests

<b>Yapısal boyut testleri</b> Structural dimension tests	: EN 60811-1-1
<b>Mekanik testler</b> Mechanical tests	: EN 50289-3, EN 50290-2
<b>Elektriksel testler</b> Electrical tests	: EN 50289-1
<b>Çevre şartları testleri</b> Environmental tests	: EN 50289-4
<b>Yangın performans testleri</b> Fire performance tests	: IEC60332-1, EN50265-2-1

\* Standart ambalajlama  
100 mt ye kadar Karton yada PVC makara, 100 mt den fazla boylar uygun PW makaralarda

\* Standard packaging  
Up to 100 mt cardboard or PVC Spool, more than 100 mt suitable PW Drums